

PRODUCT DATA SHEET

Product	Black Satin Paint
Type	A dense, satin black paint, based on high quality alkyd resins.
Intended Use	For all interior or exterior woodwork or metal when a dense satin black is required.
Special Features	Pigmented with carbon black for good opacity.
Preparation	The surface must be clean, smooth, sound, dry and free from wax, dust and contaminants. If the wood is bare, apply the appropriate primer. The Satin Matt may be used as an undercoat. Existing coatings should be cleaned with Rustin's Surface Cleaner , White Spirit, detergent or sugar soap and sanded lightly to provide a key prior to painting.
Application	Apply evenly with a good quality brush. For spray application, thin with White Spirit.
Coats	1 coat is usually sufficient. A second coat may be applied if required.
Drying Time	6-8 hours depending on temperature and humidity.
Re-coating Time	6-8 hours.
Application Temp.	Ideally 15-25°C.
Coverage	12 -14sq.m per litre per coat.
Maintenance	The surface may be cleaned with a mild detergent solution and White Spirit as necessary. Further applications may be made after cleaning.
Compatibility	May be applied over solvent and acrylic paint.
Settlement	STIR WELL BEFORE USE. Otherwise it may dry with a gloss finish.
Shelf-life/Storage	Many years if stored in original tightly closed container in normal conditions.
Hazards	Flammable. Keep out of reach of children. Use only in well ventilated areas. Keep away from sources of ignition – no smoking. Avoid contact with skin and eyes. After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent or White Spirit. A full Safety Data Sheet is available upon request.
Clean-Up	Clean brushes whilst wet with White Spirit or Rustin's Brush Cleaner . Remove excess product from brushes before cleaning. Hard brushes can be cleaned with Rustin's Brush Remover .
Sizes	125ml 250ml 500ml 1 litre 2.5 litre 5 litre